

# Specification Nordic Bronze

CuSn4



Nordic Bronze

## CW 405K

### Typical use

Architecture, eg. roofing, facades,  
window and door frames, decoration.

### Dimension:

Width range	max. 800 mm
Thickness range	0,6...2,0 mm
Coils	4000 kg
Sheet length	max. 6000 mm

### Physical properties:

Density	8,86 kg/dm <sup>3</sup>
Thermal expansion	17*10 <sup>-6</sup> 1/K (ΔT 100°C = 1,7mm/m)

### Chemical Composition %:

Tin (Sn)	3,5-4,5
Phosphorus (P)	0,01-0,4
Copper (Cu)	Rem.

### Fabrication properties:

Formability	Excellent
Soldering	Excellent
Brazing	Excellent
Resistance welding	Good
OA welding	Fair

### Mechanical properties:

The material fulfils the requirements of standard EN 1172:2011(E).

Designation			Tensile strength $R_m$		0,2 % proof strength $R_{p0,2}$		Elongation $A_{50mm}$	Hardness HV	
Material symbol	Material number	Material condition	N/mm <sup>2</sup> min.	N/mm <sup>2</sup> max.	N/mm <sup>2</sup> min.	N/mm <sup>2</sup> max.	% min.	min.	max.
Cu-DHP CuZn0,5	CW024A CW119C	R220	220	260	-	140	33	-	-
		H040	-	-	-	-	-	40	65
		R240	240	300	140	-	8	-	-
		H065	-	-	-	-	-	65	95
		R290	290	-	250	-	-	-	-
		H090	-	-	-	-	-	90	-
CuSn0,15	CW117C	R250	250	320	200	-	9	-	-
		H060	-	-	-	-	-	60	90
		R300	300	370	250	-	4	-	-
		H085	-	-	-	-	-	85	110
CuAl5Zn5Sn1	CW309G	R400	400	-	170	-	45	-	-
		H080	-	-	-	-	-	80	-
CuSn4	CW450K	R290	290	390	-	190	40	-	-
		H070	-	-	-	-	-	70	100
CuZn15	CW502L	R310	310	370	200	290	10	-	-
		H090	-	-	-	-	-	90	115